

LIQUID FILLED GAUGES



Glycerine in these gauges smooths out pulsations and protects the mechanism from corrosive environments. When used with media that attacks brass or with high pressures, all stainless steel movement & socket are offered. Lenses are Acrylic.



Meets ANSI accuracy standard B40.1[3-2-3%] except for the 6" series which have a 1% full scale accuracy. Dials are standard PSI/Bar with legend 100xkPa; 6" Models are PSI. 1/8" NPT is standard fitting on 1" gauges, optional on some 2" gauges. 1/2" NPT is standard on all larger models. Special fittings available on some models at extra cost.

Series GB Filled Stainless Steel Case, Brass Internals

Dia	Pressure Range	LM	CB	Acc. PM KIT	Detail
1"*	15, 30, 60, 100, 160, 200, 300, & 600psi 1000, 2000, 3000, 4000, 5000psi V & C	No	Yes	BPM	
2"***	15, 30, 60, 100, 160, 200, 300, & 600psi 1000, 2000, 3000, 5000psi V & C	Yes	Yes	BPM/FF	
2"*	15, 30, 60, 100, 160, 200, 300, 400, & 600psi 1000, 1500, 2000, 3000, 4000, 5000, 6000psi, V & C 10000 & 15000psi	Yes	Yes	BPM/FF	
4"	15, 30, 60, 100, 160, 200, 300, 400, & 600psi 1000, 1500, 2000, 3000, 4000, 5000, 6000psi, V & C 10000 & 15000psi	Yes	Yes	BPM/FF	

4" LM Standard fitting 1/2", 1/2" available

*Not available: LM600, 1000, 2000, 3000, V&C CB4000

**Not available: LM 4000, 5000, 6000 CB4000

Series GS Filled Stainless Steel Case & Internals

Dia	Pressure Range	LM	CB	Acc. PM KIT	Detail
1"	15, & 30 psi V & C 60, 100, 160, 200, 300, & 600 psi 1000, 2000, 3000, 4000, 5000, & 6000 psi V & C	Yes	Yes	BPM/FF	
2"	15, & 30 psi V & C 60, 100, 160, 200, 300, 600 psi 1000, 2000, 3000, 4000, 5000, 6000 psi	Yes	Yes	BPM/FF	
2"	15, & 30 psi V & C 60, 100, 160, 200, 300, 400 & 600 psi 1000, 1500, 2000, 3000, 4000, 5000, & 6000 psi V & C 10000 & 15000 psi	Yes	Yes	BPM/FF	
4"	15, 30, 60, 100, 160, 200, 300, 400, & 600psi 1000, 1500, 2000, 3000, 4000, 5000, 6000psi, V & C 10000 & 15000psi	Yes	Yes	Yes	
6"*	15, 30, 60, 100, 160, 200, 300, 400, & 600psi 1000, 1500, 2000, 3000, 4000, 5000, 6000psi	Yes	Inq	Inq	
LM	10000 & 15000psi, V & C	Yes	Inq	Inq	
STD	20000psi	Yes	Inq	Inq	

6" Options: If 6" is ordered dry, deduct Upgrade accuracy to 1% Dry or 1% Wet add.

*Secondary stock - Please call for delivery/availability. **Inquire
 V-Vacuum C -Compound LM-Lower/Bottom mount CB-Center Back Mount

PANEL MOUNTING KITS - center back liquid filled gauges only

Desc	1½"	2"	2½"	4"	Detail
------	-----	----	-----	----	--------

FF - Front Flange (specify 3 hole or "holeless") No Yes Yes Yes
 BPM - U-Clamp (bracket & screws) Yes Yes Yes Yes
 * Secondary stock - Please call for delivery/availability. **Inq** - Inquire
V - Vacuum, **C** - Compound, **LM** - Lower/bottom mount
CB - Center back mount, **PM** - Panel Mount

SERIES HB FILLED BRASS CASE & INTERNALS

Dia.	Pressure Range	LM	CB*	Detail
2 1/2"	15, 30, 60, 100, 160, 200, 300, 400 & 600 psi	Yes	Yes	
	1000, 2000, 3000 & 5000 psi	Yes		
	10000 psi	Yes		

*Not Available in 15 psi and over 400 psi