

SPECIAL PURPOSE GAUGES & ASSEMBLIES

CONTRACTOR GAUGE

These General purpose dry gauges are popular in the HVAC & plumbing trades, or for anyone using media compatible with brass/bronze. Siphon & valve are suggested for use with steam. Stainless steel case and lens ring. Brass/bronze internal working parts and 1/2" lower mount socket. ANSI accuracy Grade A [2-1-2%]. Pointer is adjustable.

Series SB-Dry, Stainless Case, Brass Internals

Dia	Case	Int	Ranges	Detail
-----	------	-----	--------	--------

4" SS BR 15, 30, 60, 100, 160, 200, 300, 400, & 600 psi, V & C

SLUMP GAUGE

This glycerin filled 4" gauge was designed for use on concrete ready-mix trucks. It has lower socket with special rear mounting studs. "L" clamps & wing nuts. Increments & numbers over 4500 psi & message "Do Not Exceed 5000 PSI" printed in red. Set pointers to be available shortly as extra cost option.

Series PGB404QLM-S Slump Gauge

Dia	Socket	PSI	Case	Internals	Socket	Detail
-----	--------	-----	------	-----------	--------	--------

4" 1/2" 5000 Stainless Steel Brass/Bronze

REFRIGERATION GAUGES

For R-12 (Old) or R-134 (New) Refrigerants. ABS plastic cases with internal parts and 1/8" socket of brass/bronze. twist on/off poly lens allows easy recalibration. Low range has retard to 300 psi. R-12 & R-134 models are not interchangeable and must be used with the appropriate refrigerant.

Series RNB-Dry Plastic Case, Brass Internals

Dia	Case	Type	Range	Specify Refrigerant	Detail
-----	------	------	-------	---------------------	--------

2" RED High 0 - 500 psi R-12/R-134

2" BLUE Low 30-0-120/300 psi R-12/R-134

GAS TEST GAUGE ASSEMBLIES & COMPONENTS

Series GT-Dry, Steel Case, Brass Internals

15 psi	Available
30, 60 or 100 psi range, assembly	Available
Manifold block only	Available
Air valve & Cap	Available

AMMONIA GAUGES

Gauges have steel internal movement, socket and case for use with anhydrous ammonia, nitrogen and other liquid fertilizers or ammonia based chemicals. Accuracy meets ANSI Standard B40.1. Socket 1/2".

Series AI-Dry, Steel Case & Internals

Application	Dia	Range	Model	Detail
Agriculture	2"	60, 150 or 400 psi	PAI	
Industrial	2"	30-0-160 or 30-0-300	CAI	
Industrial	3"	30-0-160 or 30-0-300	CAI	

WATER TEST GAUGE ASSEMBLY

Top mount 2" gauge with hose connection. Available with max pointer.

Series WT-Dry, Plastic Case, Brass Internals

Dia	Psi	Max Pointer	Detail
2"	300	No	
2"	300	Yes	

Swivel connection 1/2" x 1/2" FPT, available

Monel mini filter, available

2" DIAPHRAM GAUGES

For low pressure use as conventional gauges are not accurate below 10 PSI. Models have black steel case & can be adjusted under pressure. Meets ANSI code B40.1 with 3-3-3% accuracy.

Series DB-Dry, Steel Case, Brass Internals

Ranges Available				Specifications		
Single Scale	Dual Scale	Water Column	Low PSI	Model	Dia	NPT
10 Oz*	20 Oz/35"	15"WC	3*	Standard	2"	1/2"LM
15 Oz*	35 Oz/60"	30"WC	5	Pressure**	2"	1/2"LM
30 Oz*	60 Oz/100"	60"WC	10	Recalibrator	2"	1/2"CB
60 Oz*		100"WC		Vacuum**	2"	1/2"LM
100 Oz*		200"WC		Recalibrator	2"	1/2"CB
		300"WC				

NOTE: " indicates inches of water column.

* Recalibrator models only. ** Available either Pressure or * Vacuum.

Vacuum models are Recalibrator type only - secondary stock call for availability/delivery.

TON GAUGES

Ton gauges are available standard in a 4" stainless steel case with 1/2" lower mount connection either liquid filled or dry, 1% full scale accuracy. Optional cases (Phenolic Process Gauge case) and fittings available. Most ranges available, ram size and tonnage needs required. All ton gauges special order, allow 3 days for manufacturing.

CUSTOM TON GAUGES

Made to your specifications - Just call with the tons or psi and the overall ram size. delivery? Usually 1 - 2 days.

TON GAUGES (Stock Press Models)							
Dia	Socket Top Mount	Pressure Tons Force	Ram O/D	Case	Internals	Net Price	Detail
4"	1/3"	40/50/60	3" / 3 1/2" / 4"	Chrome Steel	Brass	\$14.55	
4"	1/4"	55	3 1/2"	Chrome Steel	Brass	\$14.55	

GAS TEST KIT

For testing LP or natural gas systems. Kit includes special carrying case with foam liner to protect gauge from rough handling. 3' hose with adapter and recalibratable 20 oz./35" H2O diaphragm gauge. Other standard range diaphragm gauges may be substituted at no extra charge.

GAS TEST KIT		
Complete With Case	Available	Detail
Without Case	Available	